

Quadra Specification Sheet

Instant boiling and chilled filtered water



Leading the Billi range the Quadra boiling and chilled drinking water systems are space saving, efficient and elegant.



-Lowest Energy Consumption

Billi's unique energy reclaim systems recovers waste heat energy generated by chilling water and reuses the energy to preheat the boiling water, thereby saving energy. By considering composition and construction of each component to every unit Billi achieves Australia's lowest carbon foot print. All Quadra units include a 7 day, 24 hour time switch to conserve power, alternative the Standby mode will also conserver power by powering down after a set period of non use.

-Smallest underbench footprint with largest capacities

With a focus on space saving, Billi systems are often less than half the size of comparative products, allowing you to make the most of the available area, while offering the largest capacities available in the market.

-Water cooled or air cooled options

Billi are the only manufacturer to offer both water-cooled and air-cooled options. Water-cooled systems are the most energy efficient option and Billi's heat exchange technology ensures water usage is absolutely minimal. Billi's air cooled option generates far less heat than traditional air cooled systems.

-Safety first

Billi's SplashFree boiling water delivery electronically varies the water flow, slowing momentarily to eliminate splashing as the water first enters the cup. All Billi dispensers are supplied standard with a safety switch.

-No cupboard ventilation required on water cooled models

The Billi Quadra watercooled units do not require cupboard ventilation or a cooling fan

-Adjustable chilled temperature

A simple adjustment allows the chilled water temperature to be raised to 15 C or lowered to 6 C for perfectly chilled, refreshing drinks, with your required temperature being quickly reached and maintained

—New unprecedented tap range.

Billi now offering a choice of 4 tap styles.

—Australian designed, manufactured and owned.



Optional XT Touch Tap













Quadra Specification Sheet

Specifications and guide to model selection

Product Number	Model Name	•	very Boiling water o. of delivery cups per hour	Chilled water delivery cups per hour	current draw amps	height mm	width mm	depth water-cooled mm	depth air-cooled* mm
904010	Quadra Compact	20	100	150	10	340	315	365	410
904020	Quadra 420	25	120	175	10	340	315	465	510
904040	Quadra 440	40	150	175	10	340	315	465	510
904060	Quadra 460	60	180	175	10	340	315	465	510
904100	Quadra 4100	100	250	175	15	340	315	465	510
904180	Quadra 4180	180	350	175	20	340	315	465	510

Power supply

Most Quadra models require a standard 10 Amp power outlet. Quadra 4100 model requires a 15 Amp power outlet while the Quadra 4180 requires a 20 Amp power outlet. All models are supplied with a 1 metre flex cord and plug.

Water supply

A single 15mm (1/2") stop-top (not supplied) with a male thread should be installed in an easily accessible position. Water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa.

Warranty

All components of the Billi Quadra are covered by a 24 month warranty. Filter cartridges are a consumable and are not covered by warranty, as water conditions and usage vary.

Certifications

Every Billi drinking water appliance is manufactured under a certified quality control system. The Billi Quadra has been tested and complies with all required standards including: Watermark Licence Number 21525; Tested to; AS3498 and AS/NZS4020; Victorian Electrical Safety Act 1998 Approval Number CS100600V, AS/NZS ISO 9002; AS1428 Accessibility Design Requirements; Section J6 of the BCA; Certificate Number QEC 11627; C-Tick approved.

Technical Advice

Contact Billi Pty Ltd on 1300 300 316

Billi

Billi Pty Ltd 42 Lucknow Crescent Thomastown Victoria 3074 Australia Telephone +613 9469 0400 Facsimile +613 9649 0400 Website www.billi.com.au

As Billi Pty Ltd has a policy of continual improvement, all details are subject to change without notice. All goods sold are subject to our standard terms and conditions.

Filtration

Billi's premium filters ensure that health threatening pollutants and impurities such as sediment, chemicals, heavy metals, chlorine and pesticides are safely removed leaving you with refreshingly clean drinking water. All Billi cartridges are certified by global public safety agency NSF International*.

Filter changes are made simple by our swing-change system and replacement cartridges are available online at www.billi.com.au. Optional sub filters are available.

Options and accessories

- Dispenser Styles: The Billi Quadra is supplied standard with the XL Levered tap pictured below. Style options are the XT Touch Tap, XR Remote Tap and the QL Quadra Levered Tap.
- Dispenser Finishes: Standard finish for the Billi Quadra Dispenser is Bright Chrome.
 Optional finish— Brushed Chrome or Black Chrome.
- Billi Font: Allows the Billi Quadra to be located away from sink areas.
 Finished in polished Stainless Steel, optional brushed or black chrome finish available.
- Dispenser Riser: 70mm dispenser extension - supplied standard with the Billi Font.
- Tubing Extension Kit: Allows the dispenser to be offset from the under bench unit by up to 2 metres.

1 cup = 170ml. Based on the initial number of cups of boiling water immediately available, drawn one cup every 10 seconds.

Consideration may be needed for usage patterns and draw-off methods.

*When specifying aircooled models, simply change the 904 to 905 and add AC after the description.

Preferred installation layout



